

JUN 25 1981

JAN 14 1982
Dpm 22325

DeSOTO, INC.
MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

NPCA 1-72

SECTION I

DeSOTO, INC.
Administrative and Research Center

1700 South Mt. Prospect Road
Des Plaines, Illinois 60018

Emergency Telephone 312-391-9000

Product Class EPOXY

Manufacturers Code Identification
515 X 347

Trade Name SUPER KOROPON ELECTRO
FR PRIMER

Date of Prep
6/19/81

***** SECTION II-HAZARDOUS INGREDIENTS *****

INGREDIENT	PERCENT BY WEIGHT	PPM	TLV MG/M ³	LEL	VAPOR PRESSURE @20° C.
Silica - Crystalline	30	-	0.3*	NA	NA
Calcium Chromate Pigment	5	-	-	-	-
Cr - Chromium	-	-	0.05	NA	NA
Toluene-Skin	< 5	100	375	1.2	35
Cyclohexanone	5	50	200	1.1	3.4
Butyl Acetate	30	150	710	1.7	8.0

THIS INFORMATION IS CONFIDENTIAL AND
IS THE PROPERTY OF DeSOTO, INC. IT IS
DISCLOSED ONLY FOR THE PURPOSES
REQUIRED BY LAW. NO OTHER USE OR
DISCLOSURE IS AUTHORIZED.

* Total

NA = Not Applicable

***** SECTION III-PHYSICAL DATA *****

PROPERTY	MEASUREMENT
Boiling Range	232-313° F. 111-157° C. @760 MM Hg
Vapor Density	X Heavier Lighter Than Air
Weight Per Gallon	11.0 lbs.
Percent Volatile By Volume	58.3
Evaporation Rate	Faster X Slower Than Ether

***** SECTION VII-SPILL OR LEAK PROCEDURES *****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Avoid breathing vapors. Ventilate area. Remove with inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state and federal regulations. Incinerate in approved facility. Do not incinerate closed containers.

***** SECTION VIII-SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION: In outdoor or open areas use NIOSH approved mechanical filter respirator.

In restricted ventilation areas use NIOSH approved chemical-mechanical filters.

In confined areas use NIOSH approved air line type respirators or hoods.

VENTILATION: Where employees may be exposed, provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients in Section II below recommended (ACGIH) or regulated (OSHA) limit. Where employees will not be exposed, keep LEL in Section II below 25% of limit.

PROTECTIVE GLOVES: Recommended X Required

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

***** SECTION IX-SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F. Store large quantities in buildings designed and protected for storage of flammable liquids.

OTHER PRECAUTIONS: Do not take internally. Containers should be grounded when pouring. Avoid free fall of liquid in excess of a few inches.

Do not sand, flame cut, braze or weld the dry coating without NIOSH approved respirator or appropriate ventilation.

Observe all precautionary label warnings.

Prepared By:
R. A. Prokop